





Sechskantmuttern mit Klemmteil, selbstsichernd DIN-EN-ISO 7042-8 (alt: DIN 980-8), verzinkt, Form V, farblos passiviert.

Maß d [mm]	Maß s [mm]	Maß e [mm]	Maß m [mm]	Maß h [mm]	VPE [Stück]	
M6	10	11,05	3,3	6,0	100	964976800
M8	13,0	14,38	4,4	8,0	100	964976801
M10	17,0	18,90	5,5	10,0	100	964976802
M12	19,0	21,10	6,6	12,0	100	964976803
M14	22,0	24,49	7,7	14,0	100	964976804
M16	24,0	26,75	8,8	16,0	100	964976805
M20	30,0	32,95	11,0	20,0	50	964976806
M24	36,0	39,55	13,2	24,0	50	964976807



Sechskantmuttern, selbstsichernd DIN-EN-ISO 10511-8 (alt: DIN 985-8), verzinkt, farblos passiviert, Klemmteil mit nicht-metallischem Einsatz, Reibschluss durch Poly-Stop-Scheibe.


Maß d [mm]	Maß s [mm]	Maß e [mm]	Maß m [mm]	Maß h [mm]	VPE [Stück]	
M5	8,0	8,79	3,2	5,0	100	964976752
M6	10,0	11,05	4,0	6,0	100	964976753
M8	13,0	14,38	5,5	8,0	100	964976754
M10	17,0	18,90	6,5	10,0	200	964976755
M12	19,0	21,10	8,0	12,0	100	964976756
M14	22,0	24,49	9,5	14,0	100	964976757
M16	24,0	26,75	10,5	16,0	100	964976758
M20	30,0	32,95	14,0	20,0	50	964976760
M24	36,0	39,55	15,0	24,0	25	964976762



### Ringmuttern

Ringmuttern DIN 582, verzinkt.

Maß d [mm]	Maß d1 [mm]	Maß d2 [mm]	Maß d3 [mm]	Maß h [mm]	Zul. Belastung [daN]	Gewicht [kg]	
M10	45	25	25	45	230	0,09	971963056
M12	54	30	30	53	340	0,16	971963057
M16	63	35	35	62	700	0,24	971963059



### Schmiernippel

Kegelschmiernippel DIN 71412 - AM 8 x 1, verzinkt.

Ausführung	Maß d [mm]	VPE [Stück]	
H1 gerade	M6 x 1	50	225551078
H1 gerade	M8 x 1	50	225551079
H1 gerade	M10 x 1	50	225551080
H2 45°	M10 x 1	50	225551083
H3 90°	M6 x 1	50	225551081

